



SS102A, SS105B, SS106 Transformers PO001 Electric Door Opener Specification Sheet

IL127
Section A
Rev. 12 - 03/2010

PO001 ELECTRIC DOOR OPENER

TekTone®'s PO001 Electric Door Opener is for use in unlocking and locking doors from a variety of TekTone® remote stations. The door opener can be installed in place of the door lock, or on a door jamb with various door lock sets. The PO001 is a normally locked type with heavy duty coils, and operates on 8-16 VAC or 3-6 VDC. The unit features a flat face with satin zinc finish and solid brass locking latch for long wear. Model PO001 is reversible for mortise-type locks and latches up to 1/2" width and throw, and is ideal for most narrow jamb mortise-type installations. Depending on the specific job requirements, the PO001 can be reversed for right or left-hand door installation.



DIMENSIONS

Faceplate: 1.25" × 5.875" (31.8 mm × 149 mm)
Case width: 0.9375" (24 mm)
Case depth: 1.4375" (37mm)
Latch opening: 1.375" (35 mm)

SS102A, SS106 TRANSFORMERS

TekTone®'s SS102A and SS106 Class 2 Transformers offer compact, easy-to-install low voltage AC power sources for use with various TekTone® intercom systems. Both transformers are UL® Listed and will safely take themselves offline when overheated. The transformers are constructed for easy installation in a standard 1/2" knockout or for surface installations, and may be used in plastic or metal boxes. Primary wire connections are made using the pre-stripped pigtails and ground wire; secondary connections are made using screw terminals.



SPECIFICATIONS

SS102A 120 VAC primary, 16 VAC 10 VA secondary
SS106 120 VAC primary, 8 VAC 20 VA
16/24 VAC 30 VA secondary

SS105B TRANSFORMER

TekTone®'s SS105B Class 2 Plug-In Transformer was designed for quick and easy installation in environments where pigtail-type transformers are impractical or unsightly. It is particularly suitable for use in office or home installations, or in areas where the transformer must be exposed. The plug-in installation saves time and money over standard transformer installation requiring hand wiring and long runs from hard-to-get-at areas. TekTone®'s unit installs quickly and easily to existing outlets and includes an extra long replacement screw for secure attachment to a faceplate.



SPECIFICATIONS

117-16 VAC 10 VA Plug-in type, UL® Listed

www.tektone.com

277 Industrial Park Road • Franklin, NC 28734 • tektone@tektone.net
Phone: (828) 524-9967 • Fax: (828) 524-9968 • Tech Support: Choose option 2 • Sales: Choose option 3
TekTone®'s quality system is registered by UL® to the ISO 9001 standard. (Reference #10001510.)