




# PK601A 24 VDC Power Supply Specification Sheet

IL420  
Section D  
Rev. 11-08/2010



**PK601A**  
**24 VDC Power Supply**

## FEATURES

The PK601A is a 24 VDC power supply designed to power auxiliary signaling devices used in TekTone® emergency call systems. The unit provides a filtered 24 VDC output rated at 1 amp.

Although specifically designed for use with emergency call systems, the PK601A may also be used as a DC silent door opener adapter in TekTone® apartment entrance systems.

- Easy installation
- Low-voltage operation
- Multiple applications
- Precision engineering

## SPECIFICATIONS

Dimensions:	Height:	5" (127mm)
	Width:	2.375" (60mm)
	Depth:	2.25" (57mm)
Construction:	Quality electronic components mounted on a PC board encased in a rugged extruded aluminum housing	
Connections:	Screw terminals	
Mounting:	Surface	
Output voltage:	24VDC	
Output current:	1 amp	
Power Requirements:	16VAC, 30 VA	

## ARCHITECTS' AND ENGINEERS' SPECIFICATION

The power supply shall be TekTone® PK601A, or approved equal, and shall provide 24 VDC power to auxiliary signaling devices used in specified TekTone® emergency call systems.

The PK601A shall also be suitable for use as a DC silent door opener adapter in specified TekTone® apartment entrance systems.

The PK601A circuitry shall be housed in a rugged extruded aluminum case. Screw terminals shall be provided for installation wiring.

[www.tektone.com](http://www.tektone.com)

277 Industrial Park Road • Franklin, NC 28734 • [tektone@tektone.net](mailto:tektone@tektone.net)  
Phone: (828) 524-9967 • Fax: (828) 524-9968 • Tech Support: Choose option 2 • Sales: Choose option 3  
TekTone®'s quality system is registered by UL® to the ISO 9001 standard. (Reference #10001510.)