




PK601A 24 VDC Power Supply Specification Sheet

IL420
Section D
Rev. 10-03/2008



PK601A
24 VDC Power Supply

FEATURES

The PK601A is a 24 VDC power supply designed to power auxiliary signaling devices used in TekTone® emergency call systems. The unit provides a filtered 24 VDC output rated at 1 amp.

Although specifically designed for use with emergency call systems, the PK601A may also be used as a DC silent door opener adapter in TekTone® apartment entrance systems.

- Easy installation
- Low-voltage operation
- Multiple applications
- Precision engineering

SPECIFICATIONS

| | | |
|---------------------|---|---------------|
| Dimensions: | Height: | 5" (127mm) |
| | Width: | 2.375" (60mm) |
| | Depth: | 2.25" (57mm) |
| Construction: | Quality electronic components mounted on a PC board encased in a rugged extruded aluminum housing | |
| Connections: | Screw terminals | |
| Mounting: | Surface | |
| Output voltage: | 24VDC | |
| Output current: | 1 amp | |
| Power Requirements: | 16VAC, 30 VA | |

ARCHITECTS' AND ENGINEERS' SPECIFICATION

The power supply shall be TekTone® PK601A, or approved equal, and shall provide 24 VDC power to auxiliary signaling devices used in specified TekTone® emergency call systems.

The PK601A shall also be suitable for use as a DC silent door opener adapter in specified TekTone® apartment entrance systems.

The PK601A circuitry shall be housed in a rugged extruded aluminum case. Screw terminals shall be provided for installation wiring.

www.tektone.NET

277 Industrial Park Road • Franklin, NC 28734 • Phone (828) 524-9967 • Fax (828) 524-9968
Email: tektone@tektone.net • Technical Assistance Email: teksupt@tektone.net
TekTone®'s quality system is registered by UL® to the ISO 9001:2000 standard. (File #A10766.)