

### Features

- Sensitive touch activation
- Oxygen tent safe
- Ideal for geriatric use
- Momentary, air-activated switch
- Adjustable bed clip(s)
- UL® 1069 Listed

### Description

The TekTone® SF301G Call Cord is for use with Tek-CARE® nurse call systems and wireless emergency call systems where ¼" phono jacks are used.

The SF301G Call Cord is specifically designed for use in geriatric and oxygen environments, but may also be used in general applications. To place a call, the patient applies slight pressure to the squeeze bulb using any part of the body. The force of air through the vinyl tubing closes a switch in the plug, thus placing a call. An adjustable bed clip is supplied for the SF301G and is attached to the call cord.

### Required Components

Tek-CARE®3000 Nurse Call System  
with SF121 or SF122 Patient Stations

or

Tek-CARE®400 GEN3 Nurse Call System  
with SF121 or SF122 Patient Stations

or

Tek-CARE®500 Wireless Nurse Call System  
with SF521UL or SF523UL Room Stations

or

Tek-CARE®120 Nurse Call System  
with SF121 or SF122 Room Stations

or

Tek-CARE®300II Nurse Call System  
with SF380A Patient Stations

or

Tek-CARE®NC200N or NC150N Nurse Call Systems  
with IR151B or IR152B Patient Stations

or

Tek-CARE®NC110N Nurse Call System  
with SF100C or SF102 Patient Stations



SF301G Call Cord

### Specifications

Switch:	Momentary contact, air activated
Plug:	Stainless steel
Cord:	Vinyl tubing
Electrical:	Rated current 1/3 AMP, 24 VAC-VDC
Dimensions:	Cord: 6' long (1.83 m) Plug: 1.25" long (32 mm) Bulb: 1.5" diameter (38 mm)

### Listings



UL® 1069 Listed and cUL® Listed to CSA  
C22.2 No. 205; UL® File Number E71599.