

Features

- UL® 1069 Listed
- Simple and flexible operation
- Call-placed indicator
- Call cancel at point of origin
- Flame retardant (UL® 94V-0) plastic faceplate
- 1.1" (28 mm) wide pull-down lever
- Washable TPU plastic pull-cord kit is included

Description

The SF340B Emergency Switch is for use in any location where activation of an emergency signal is required. All electronic components are mounted on a circuit board. The specially mounted LED is completely sealed in plastic.

Due to the flexibility of its design, the SF340B may be used as a pull-cord emergency switch, a pull-down activated emergency switch, or a staff assist emergency call switch. The pull-cord supplied may be used for emergency call activation or, if desired, the large 1.1" (28 mm) red pull-down lever may be used.

Dome light and system annunciation vary according to the manner in which the SF340B is connected.

Listings



UL® 1069 Listed; UL® File Number E71599.

Specifications

- Dimensions: 4.8"H × 3.2"W × 1.2"D
(122 mm × 81 mm × 30 mm)
- Construction: Flame retardant (UL® 94V-0) plastic faceplate. Switch and electronic components are circuit board mounted
- Connections: Plug-in connectors
- Housing: Single-gang ring (IH357) with square box (IH358), or exact equal



SF340B Emergency Switch
(cord not shown)

Applicable Components

Tek-CARE® 400 P5 Nurse Call System
Tek-CARE® 300II Nurse Call System