



# SF154B Emergency Call Switch Specification Sheet

IL647  
Section D  
Rev. 5 - 09/2010



**SF154B**

## ARCHITECTS' AND ENGINEERS' SPECIFICATION

The SF154B shall use a push button switch with DPDT (double-pole double-throw) contacts. The switch shall provide for positive visual indication of activation. Wiring pigtails shall be provided for connection to both normally open contacts. The switch shall be mounted on an attractive, flame retardant (UL® 94V-0) plastic panel which is designed to fit onto a single-gang electrical box.

## FEATURES

The SF154B Emergency Call Switch features a push button switch with DPDT (double-pole double-throw) contacts which are available via wire pigtail. The switch comes pre-wired with both normally open terminals available individually. The switch has a mechanical eye arrangement inside, which provides for positive indication of activation without the need for external power. The switch features push-on push-off operation. The SF154B is designed as a single-gang (UL® 94V-0) plastic panel that fits a standard single-gang electrical box.

- Simple operation and installation
- Attractive, flame retardant (UL® 94V-0) plastic panel
- Fits standard single-gang electrical box
- Visual indication of activation

## SPECIFICATIONS

Dimensions:    Height: 4.5" (115 mm)  
                         Width: 2.8125" (72 mm)  
                         Depth: 1.5" (39 mm)  
                         Projects: 0.8125" (21 mm)  
                         (From mounting surface)

Construction: Flame retardant (UL® 94V-0) plastic  
Housing: Single-gang ring or box.

## REQUIRED COMPONENTS

LI381	Corridor Light
SS106	Transformer

[www.tektone.com](http://www.tektone.com)

277 Industrial Park Road • Franklin, NC 28734 • [tektone@tektone.net](mailto:tektone@tektone.net)  
Phone: (828) 524-9967 • Fax: (828) 524-9968 • Tech Support: Choose option 2 • Sales: Choose option 3  
TekTone®'s quality system is registered by UL® to the ISO 9001 standard. (Reference #10001510.)