

Features

- UL[®] 1069 Listed
- Simple and flexible operation
- Call-placed indicator
- Call cancel at point of origin
- Flame-retardant (UL[®] 94V-0) plastic faceplate
- 0.9" diameter (23 mm) red mushroom-style button

Description

The SF339 Emergency Switch includes a locking mushroom-style switch, and is for use in any location where activation of an emergency signal is required. All electronic components are mounted on a circuit board, including a reliable industry-proven DPDT switch for circuit initiation. The DPDT switch and the indicator LED are completely sealed in plastic.

The SF339 may be used as an emergency switch or as a staff-assist emergency call switch. The large mushroom-style button is easily activated, so that calls may be placed using an elbow, shoulder, etc., when using the hands is inconvenient or inappropriate. Calls are cancelled by turning the mushroom-style button clockwise.

Dome light indication and system annunciation vary according to the manner in which the SF339 is installed.

Specifications

Dimensions:	Height:	4.5"	(114.3 mm)
	Width:	2.8125"	(71.4 mm)
	Overall Depth:	2"	(50.8 mm)
	Projects Front:	0.95"	(24.1 mm)
	Projects Rear:	1.05"	(26.7 mm)
Construction:	Flame-retardant (UL [®] 94V-0) plastic faceplate. DPDT switch and electronic components are circuit board mounted.		
Connections:	Plug-in connectors.		
Flush Housing:	Single-gang ring with square box; for Tek-CARE500 use plastic single-gang box with minimum 2.875" × 2.125" opening.		
Surface Housing:	TekTone [®] IH527 plastic back box for Tek-CARE [®] 500.		



SF339 Emergency Switch

Listings



UL[®] 1069 listed; UL[®] File Number E71599.

Applicable Systems

Tek-CARE[®]400 P5 Nurse Call System
 Tek-CARE[®]300II Nurse Call System
 Tek-CARE[®] NC200, NC150, NC110 Nurse Call Systems
 Tek-CARE[®]500 Wireless Nurse Call System