



SF401A Oxygen-Safe Call Cord Specification Sheet

IL767
Section E
Rev. 4-08/2010



SF401A

FEATURES

The TekTone® SF401A single call cord is for use with the Tek-CARE®NC300II nurse call system, where 8-pin DIN jacks are used. The SF401A is an oxygen safe call cord that is certified safe for use by all patients receiving oxygen therapy. This waterproof and impact resistant call cord has a completely sealed push button.

- UL® 1069 Listed
- Oxygen safe
- Impact resistant and waterproof
- Small, lightweight pendant fits comfortably in hand
- Bed clips included

SPECIFICATIONS

Connection: 8-pin DIN plug
 Construction: SPST1-A switch
 Integral brass, fine silver contacts
 1 AMP, 115 watt maximum, AC
 Dimensions: 7' (2.13 m) long polyvinyl-covered cord

REQUIRED COMPONENTS

Tek-CARE®NC300II	Nurse Call System
IR319B or IR320B	Patient Stations

ARCHITECTS' AND ENGINEERS' SPECIFICATION

Call cords shall be TekTone® SF401A or approved equal. Model SF401A shall provide one molded push button, shall be waterproof, and shall be suitable for use in oxygen environments.

The momentary-contact push button cordset shall be encased in a molded, shock-proof plastic shell. It shall be connected to a 7' (2.13 m) long polyvinyl covered cord with an integrally molded 8-pin DIN plug.

The SF401A shall be UL® 1069 Listed.

www.tektone.com

277 Industrial Park Road • Franklin, NC 28734 • tektone@tektone.net
 Phone: (828) 524-9967 • Fax: (828) 524-9968 • Tech Support: Choose option 2 • Sales: Choose option 3
 TekTone®'s quality system is registered by UL® to the ISO 9001 standard. (Reference #10001510.)