

Features

- Provides visual indication of system calls.
- White LEDs are selectable for warm or cold hues
- Choice of red & white or blue & white LED options
- Provides 6 connection points for patient stations, 2-button pull-cord stations, and duty stations.
- Long lasting LEDs; no bulb replacement required.
- UL/cUL® 1069 and UL® 2560 Listed.
- RoHS Compliant.

Description

The LI122UN Room Controller with Dome Light provides the interface to a duty station, patient station, and two-button pull-cord stations, plus visual indication of calls originating from them. The LI122UN also provides communication to and from the central equipment module.

The LI122UN model room controller has slide switches to manually select the two dome colors as White/Red or White/Blue and the tone of the White color as Warm White or Cool White.

The LI122UN Room Controller indicates higher priority calls by flashing the two red or blue LEDs. Lower priority calls are indicated by steady illumination of the two white LEDs. If an emergency and lower priority call are placed in the same location at the same time, the red emergency LEDs will flash while the white LEDs will maintain a steady illumination.

The LI122UN Room Controller can also be configured as a zone light to indicate calls that originate from the stations assigned to a particular zone.

Listings



UL® 1069, UL® 2560, and cUL® listed to CSA C22.2 No. 205; UL® File Number E71599.



RoHS Compliant.



LI122UN Room Controller with Dome Light

Specifications

Dimensions:	4.8"H × 5.0"W × 2.76"D (122 mm × 127 mm × 70 mm)
Environment:	5%–95% non-condensing humidity; 0°C–60°C
LEDs:	2V 20mA per LED
Base:	Flame-retardant (UL® 94HB) plastic
Lens:	Flame-retardant translucent polycarbonate plastic
Mounting:	Fits standard one- or two-gang box with one- or two-gang ring
Connections:	6-pin and 8-pin pigtailed connector (harness included)

Required Components

NC120 or 160 Central Equipment Module
NC415AV or NC404TS Master Station
SF121 Single Patient Station, SF122 Dual Patient Station,
SF123 Two-Button Pull-Cord Station, and/or SF125 Duty Station
PM123 Auxiliary Input Module