

Features

- Sensitive touch activation
- Oxygen tent safe
- Ideal for geriatric use
- Momentary, air-activated switch
- Adjustable bed clip(s)
- UL® 1069 Listed

Description

TekTone® SF301G and SF302G Call Cords are for use with Tek-CARE® nurse call systems and wireless emergency call systems where ¼" phono jacks are used.

SF301G and SF302G Call Cords are specifically designed for use in geriatric and oxygen environments, but may also be used in general applications. To place a call, the patient applies slight pressure to the squeeze bulb using any part of the body. The force of air through the vinyl tubing closes a switch in the plug, thus placing a call. An adjustable bed clip is supplied for the SF301G and is attached to the call cord. Two adjustable bed clips are supplied with the SF302G.

Listings



UL® 1069 Listed; UL® File Number E71599.

Specifications

Switch:	Momentary contact, air activated
Plug:	Stainless steel
Cord:	Vinyl tubing
Electrical:	Rated current 1/3 AMP, 24 VAC-VDC
Dimensions:	Cord: 6' long (1.83 m) Plug: 1.25" long (32 mm) Bulb: 1.5" diameter (38 mm)



SF301G Call Cord

Required Components

Tek-CARE®500 Wireless Nurse Call System with SF530ES or SF530UL Room Stations
or
Tek-CARE®120 or 160 Nurse Call System with SF121 or SF122 Room Stations
or
Tek-CARE®300II Nurse Call System with SF380A Patient Stations
or
Tek-CARE® NC200N or NC150N Nurse Call Systems with IR151B or IR152B Patient Stations
or
Tek-CARE® NC110N Nurse Call System with SF100C or SF102 Patient Stations