

Features

- UL® 1069 Listed
- Simple and flexible operation
- Call-placed indicator
- Call cancel at point of origin
- Flame-retardant (UL® 94V-0) plastic faceplate
- 1.1" (28 mm) wide pull-down lever
- Washable TPU plastic pull cord kit is included

Description

The SF340B Emergency Switch is for use in any location where activation of an emergency signal is required. All electronic components are mounted on a circuit board. The specially mounted LED is completely sealed in plastic.

Due to the flexibility of its design, the SF340B may be used as a pull cord emergency switch, a pull down activated emergency switch, or a staff assist emergency call switch. The pull cord supplied may be used for emergency call activation or, if desired, the large 1.1" (28 mm) red pull-down lever may be used.

Dome light and system annunciation vary according to the manner in which the SF340B is connected.

Specifications

Dimensions:	Height:	4.5"	(114 mm)
	Width:	2.8125"	(72 mm)
	Depth:	1.625"	(41 mm)
	Projects:	0.6875"	(17 mm)
		from mounting surface (including pull-down lever)	
Construction:	Flame-retardant (UL® 94V-0) plastic faceplate. Switch and electronic components are circuit board mounted.		
Connections:	Plug-in connectors.		
Housing:	Single gang ring (IH357) with square box (IH358), or exact equal.		



SF340B Emergency Switch
(pull cord not shown)

Listings



UL® 1069 listed; UL® File Number E71599.

Applicable Systems

Tek-CARE®400 P5 Nurse Call System
Tek-CARE®300II Nurse Call System