

Description

The LI404B Strobe is a high-intensity remote visual signaling device for use with TekTone® Tek-ENTRY® Apartment Entry Systems that use either the PK543A Amplifier/Relay/Power Supply or the PK205 Amplifier/Relay/Power Supply.

The unit is primarily for use in locations where hearing-impaired persons require supplemental call notification, but can be used anywhere a visual indication of an incoming call is desired. The bright strobe light flashes for approximately 15–20 seconds when an incoming call is detected.

The device can be installed in most standard single or double gang electrical boxes or similar indoor openings. It is not a weatherproof device and therefore should not be used for any outdoor applications. Installation is facilitated by the use of simple connections to the pre-mounted circuitry and a complement of mounting hardware. The LI404B Strobe Light portion meets ADA and UL® 1971 requirements.

Specifications

Dimensions:	Height:	5.5"	(140 mm)
	Width:	4.5"	(114 mm)
	Depth:	3.5"	(89 mm)
	Projects:	2.5"	(63.5 mm)
		from mounting surface	
Construction:	Attractive, flame-retardant (UL® 94V-0) plastic housing		
Strobe:	15 candela per UL® 1971		
Power:	24 VDC, 57 mA DC nominal		
Wiring:	18 gauge minimum, 750' maximum		
Installation:	Standard single or dual gang box		



LI404B Strobe

Required Components

Tek-ENTRY® Apartment Entry System
PK543A Amplifier/Relay/Power Supply
To power locally (retrofit or standalone installations), add:
PK601A 24 VDC Power Supply
SS106 Transformer

–or–

Tek-ENTRY® Apartment Entry System
PK205 Amplifier/Relay/Power Supply
PK601A 24 VDC Power Supply
SS106 Transformer