

Features

- Sensitive touch activation
- Oxygen tent safe
- Ideal for geriatric use
- Momentary, air-activated switch
- Adjustable bed clip

Description

TekTone® SF401G Call Cords are used with 8-pin DIN jack patient stations, including Tek-CARE®400 IR411-series and IR412-series patient stations, Tek-CARE®400 P5 IR411P5 and IR412P5 patient stations, and Tek-CARE®300II IR319-series and IR320-series patient stations.

The SF401G Call Cord is specifically designed for use in geriatric and oxygen environments, but may also be used in general applications. To place a call, the patient need only apply slight pressure to the squeeze bulb using any part of the body. The force of air through the vinyl tubing closes a switch in the plug, thus placing a call. An adjustable bed clip is supplied for the SF401G and is attached to the call cord.

Specifications

Switch:	Momentary contact, air activated
Plug:	Stainless steel 8-pin DIN
Cord:	Vinyl tubing
Electrical:	Rated current 1/3 amp, 24 VAC-VDC
Dimensions:	Cord: 6' long (1.83 m)
	Bulb: 1.5" diameter (38 mm)



SF401G Call Cord

Required Components

for Tek-CARE®300II Nurse Call Systems:
IR319- or IR320-series Patient Stations

for Tek-CARE®400 Nurse Call Systems:
IR411- or IR412-series Patient Stations

for Tek-CARE®400 P5 Nurse Call Systems:
IR411P5 or IR412P5 Patient Stations