

Features

- UL® 2560 Listed
- Fully supervised wireless 900MHz transmitter
- Provides standard ¼" receptacle, suitable for use with many call cord types
- Checks for cord out state
- Low battery warning before battery depletion
- Call assurance LED
- Field replaceable 3V lithium battery

Description

The SF530UL single resident bed station features the great range and reliability of 900MHz signaling. This unit can be wall mounted near any resident location for call placement. It provides a standard ¼" call cord receptacle along with a reset button. Calls are latched locally to ensure that residents receive direct staff attention. The device includes a call assurance LED as well as cord out detection. The SF530UL features a fully supervised RF link to ensure reliability and to monitor for battery low condition. The battery is a customer replaceable 3V lithium.

Listings



UL 2560 Listed; UL® File Number E71599.



SF530UL Single Resident Bed Station

Specifications

| | | | |
|------------------|---|---------|------------|
| Dimensions: | Height: | 4.5" | (114.3 mm) |
| | Width: | 2.8125" | (71.4 mm) |
| | Overall Depth: | 2.35" | (59.7 mm) |
| | Projects Front: | 0.4375" | (11.1 mm) |
| | Projects Rear: | 1.9125" | (48.6 mm) |
| Construction: | Flame-retardant (UL® 94V-0) plastic | | |
| Flush Housing: | Plastic single-gang box with minimum 2.875"× 2.125" opening | | |
| Surface Housing: | TekTone IH527 plastic back box | | |
| Battery: | 3.0V Lithium (BA505) | | |

Required Components

Tek-CARE500 Wireless Nurse Call System