

### Features

- UL® 2560 Listed
- Fully supervised wireless 900Mhz transmitter
- Low battery warning before battery depletion
- Call assurance LED
- Resident check-in capability
- Field-replaceable 3V lithium battery
- Washable TPU plastic pull cord kit is included

### Description

The SF529UL Wireless Check-In/Assistance Call Station features the great range and reliability of 900MHz signaling. This unit can be wall mounted near any resident location for call placement (stainless steel and other metal fixtures may interfere with the signal transmission).

Calls are latched locally to ensure that residents receive direct staff attention. The device includes a call assurance LED. Resident check-ins are placed by pressing the Check-In push button during set check-in times. The SF529UL features a fully supervised RF link to ensure reliability and to monitor battery state. The battery is a field-replaceable 3V lithium.

### Specifications

Dimensions:	Height:	4.5"	(114.3 mm)
	Width:	2.8125"	(71.4 mm)
	Overall Depth:	1.95"	(49.5 mm)
	Projects Front:	0.71"	(18 mm)
	Projects Rear:	1.24"	(31.5 mm)
Construction:	Flame-retardant (UL® 94V-0) plastic		
Flush Housing:	Plastic single-gang box with minimum 2.875"× 2.125" opening		
Surface Housing:	TekTone® IH528 plastic back box		
Battery:	3.0V Lithium (BA505)		



SF529UL Wireless Check-In/Assistance Call Station

### Listings



UL® 2560 Listed; UL® File Number E71599.

### Required Components

- Tek-CARE500 Wireless Nurse Call System