LI132 Dome Light and Room Controller
IL1167 Specification Sheet

Tek-CARE Nurse Call Systems • Rev. 0 - 11/2026

Features

- Provides visual indication of system calls
- Improved LED brightness
- Long-lasting LEDs; no bulb replacement required
- Automatically lights red, blue, or white when used with the latest system software
- Provides 6 connection points for patient stations, pull-cord stations, and duty stations
- Easy to wire plug-on pigtail connectors

Description

TekTone's LI132 Dome Light and Room Controller provides the interface to a duty station, patient station, or pull-cord station, and provides visual indication of calls originating from the station(s). The LI132 also provides communication to and from the central equipment module, and serves as the direct replacement for the LI122UN.

The LI132 indicates higher priority calls by flashing the LEDs of the appropriate color. Lower priority calls are indicated by steady illumination of the two white LEDs.

The LI132 can also be configured as a zone light to indicate calls that originate from the stations assigned to a particular zone.

Required Components

Tek-CARE®120 Nurse Call Systems

Optional Components

NC415G3 or NC404TS Master Station



LI132 Dome Light

Specifications

Dimensions:	4.8"H × 5.0"W × 2.76"D (122 mm ×127 mm × 70 mm)
Environment:	5%–95% non-condensing humidity; 0°C–60°C
LEDs:	2V 20mA per LED
Base:	Flame-retardant (UL® 94HB) plastic
Lens:	Flame-retardant translucent polycarbonate plastic
Mounting:	Fits standard one- or two-gang box with one- or two-gang ring
Connections:	6-pin and 8-pin pigtailed connector (harness included)

Listings

UL® 1069, UL® 2560, and cUL® listed to CSA C22.2 No. 205; UL® File Number E71599.

www.tektone.com
324 Industrial Park Road • Franklin, NC 28734 • https://www.tektone.com/contact/
Phone: 828.524.9967 • Fax: 828.524.9968 • Sales: Choose option 2 • Tech Support: Choose option 3
TekTone's quality system is registered to the ISO 9001:2015 standard.