

### Features

- UL® 1069 Listed
- Supervised
- Microprocessor design
- Solid-state multiplex circuitry
- All stations are interchangeable
- Simplified multiplex wiring using plug-in connectors
- Flame-retardant (UL® 94V-0) plastic faceplate
- Six-foot washable TPU plastic pull cord

### Description

The IR318B single patient station provides reliable two-way hands-free communication between patient and nurse, and provides for programmable privacy, paging and patient priority from the master station.

Calling the nurse is accomplished by pulling on the end of the pull cord. Solid-state LEDs on the panel indicate the call has been placed and the intercom is in use.

### Listings



UL® 1069 listed; UL® File Number E71599.



IR318B Single Patient Station

### Specifications

Dimensions:	Height:	4.5"	(119 mm)
	Width:	6.375"	(162 mm)
	Depth:	2.75"	(70 mm)
	Projects:	0.5"	(12.7 mm)
Construction:	Flame-retardant (UL® 94V-0) plastic.		
Speaker:	2.5" x 2.5" (64 mm x 64 mm)		
Connections:	Plug-in type		
Housing:	Steel City #H3BD with Steel City #3GC plaster ring, or exact equal. Horizontal mount.		
Wiring:	Multiplex		

### Required Components

Tek-CARE®300II Nurse Call System