

Features

- UL® 1069 Listed
- Oxygen safe
- Impact resistant and waterproof
- Small, lightweight pendant fits comfortably in hand
- Bed clips included

Description

The TekTone SF401A single call cord is for use with the Tek-CARE400, Tek-CARE400 P5/P5+/GEN3, and Tek-CARE300III Nurse Call Systems, where 8-pin DIN jacks are used. The SF401A is an oxygen safe call cord that is certified safe for use by all patients receiving oxygen therapy. This waterproof and impact resistant call cord has a completely sealed push button and a polyvinyl-covered cord.

Required Components

Tek-CARE400 GEN3 Nurse Call System
IR430G3, IR431G3/IR432G3, IR434G3 patient stations

Tek-CARE400 Nurse Call System
IR411, IR412, IR412EPB patient stations

Tek-CARE400 P5/P5+ Nurse Call System
IR411P5/IR421P5, IR412P5/IR422P5 patient stations

Tek-CARE300III Nurse Call System
IR319B, IR320B patient stations



SF401A Oxygen-Safe Call Cord

Specifications

Dimensions:	SF401A:	7' (2.13 m) long
	SF401A/10:	10' (3.05 m) long
	SF401A/15:	15' (4.57 m) long
	SF401A/20:	20' (6.10 m) long

Connection:	8-pin DIN plug	
Construction:	SPST1-A switch Integral brass, fine silver contacts 1 AMP, 15 watt maximum, AC	

Listings



UL® 1069 Listed and cUL® Listed to CSA
C22.2 No. 205; UL® File Number E71599.